

Item Name	TEVO-VA612GROUP-EX
	
HD Conference Camera	
Optical Zoom	12x zoom
Image Sensor	1/2.8" SONY CMOS
Effective Pixels	8.29MP
Lens	f=3.9mm-46.8mm
Aperture	F1.6-2.8
Video Format	4KP@30fps,1080P@60/50/30/25fps, 720P@60/50/30/25fps
	H.264, H.265, MJPG, YUY2, NV12
Horizontal Angle	70.82°(W)-6.48°(T)
Focus	Auto / Manual
Digital Noise Reduction	2D & 3D Noise Reduction
Exposure	Auto / Manual
Video Interfaces	HDMI, DP
Video Compression Format	H.264, H.265, MJPG, YUY2
Control Protocol	VISCA/Pelco-D/Pelco-P
Baud Rate	38400/9600/4800/2400
Control Interface	RS232 (input only), RS485, UVC1.1
Pan/Tilt Rotation	±175°, -90°~+90°
Pan Control Speed	0.1 -80°/sec
Tilt Control Speed	0.1-60°/sec
Preset Number	User can set up to 255 presets (10 presets by IR remote)
Speakerphone	
Acoustic Echo Cancellation(AE)	>65dB
Speaker Power	5W
Speaker Volume	110dB
Response	100Hz-20KHz
Pickup Range	6m(Radius)
Microphone Sensitivity	-38dBFS
SNR(Signal to Noise Ratio)	62dB
Interface	DP interface; 2x3.5mm Jack扩展麦口
Hub	
Interface	DP*2; Power interface*1; USB Type-C*1
Power Supply	DC 12V
USB Cable	3m USB cable*1

Connection Cable	5m DP cable*2
General Parameter	
Operation Systems	Windows 7 or higher; Android, Mac OS™ 10.10 or higher, Linux (Required to support UVC.)
Application Support	Compatible with Zoom, MS Teams, Skype and etc.
Input Voltage	DC 12V
Input Current	2.0A(Max)
Store Temperature	-10℃~+60℃
Store Humidity	20%~90%
Working Temperature	-10℃~+50℃
Working Humidity	20%~80%
Dimension (W*H*D)	Camera: 171.6*192.6*171.6mm; Speakerphone: 143mm*143mm*75mm; Hub: 98*98*20mm
N.W. / G.W	2.77kg/4kg(net / gross weight)